



- For workpiece positioning and stopper applications.
- Pad is made of polyurethane. The material has excellent water resistance and has low risk of hydrolysis in humid environments.
- Urethane absorbs impacts.
- All products are provided with a lock nut.

Material/Finish



	SUS
Thread Part	SCM435 Nickel Plating
Pad	Polyether Urethane (Hardness Shore A90) *1
Lock Nut	SS400 Trivalent Chromate Treatment

*1 : While polyether urethane may show yellow discoloration, the performance remains unaffected.

Dimensions

Unit : mm

Part Number	M (Coarse)		t	L ₂	D ₁	B	C	B ₁	T	h	d ₁	Mass (g)
	Nominal of Thread ◀1	Pitch										
SUS-M4	M4	0.7	4.5	0.5	3.1	7	8.1	2	2.4	3	1.6	1.6 - 3.1
SUS-M5	M5	0.8	4.5	0.5	4	8	9.2	2.5	3.2	3	2.2	3 - 6.1
SUS-M6	M6	1	4.5	0.5	4.8	10	11.5	3	3.6	3	2.6	5.6 - 11
SUS-M8	M8	1.25	5.5	0.5	6.5	13	15	4	5	4	5.1	13 - 20
SUS-M10	M10	1.5	5.5	0.5	8.3	17	19.6	5	6	4	6.9	21 - 31

Part Number	L (mm) ◀2									
	10	15	20	25	30	35	40	45	50	60
SUS-M4	●	●	●	●	●	●				
SUS-M5	●	●	●	●	●	●	●			
SUS-M6		●	●	●	●	●	●		●	
SUS-M8				●	●	●	●	●	●	
SUS-M10					●	●	●	●	●	●

- Part number specification

SUS - M5 - 40

Product Code ◀1 ◀2

Cleanroom Wash & Packaging → P.xxxx	Screw Combination → P.xxxx	Screw Length Adjustment → P.xxxx	Vibration Resistant → P.xxxx
Not Available	Available / Add'l charge	Not Available	Available / Add'l charge