
SNSTA Hex Socket Head Cap Screws (Tantalum)







Selection CAD Scleanroom wash & packaging Chemical-proof

Material/Finish



9	SNSTA
Main Body	Tantalum

Mechanical property

	Tantalum	SUS304
Tensile Strength (N/mm²)	271	520 or More
0.2% Proof Load (N/mm²)	189	205 or More
Elongation (%)	51.2	40 or More

• Values in chart are for reference only. They are not guaranteed values.

Physical property

	Tantalum	SUS304
Specific Gravity	16.65	7.93
Longitudinal Elastic Modulus (GPa)	185	193
Specific Heat (J/kg·K)	140	500
Linear Expansion Coefficient (K-1)	6.4 × 10 ⁻⁶	17.3 × 10 ⁻⁶

• Values in chart are for reference only. They are not guaranteed values.



- Tantalum hex socket head cap screws.
- Tantalum is a material characterized by excellent chemical resistance and high specific gravity.
- With excellent corrosion resistance to strong acids such as sulfuric acid, it is also resistant to aqua regia.
- The specific gravity is approximately twice that of general steel and stainless steel.
- Cleanroom wash/cleanroom packing provided. → P. XXXX

Application

FPD production equipment / Semiconductor manufacturing equipment / Printed circuit board etching devices /

Metallic surface treatment equipment and facilities / Chemical plants

Unit:mm

Part Number 1	M (Coarse)								D ₁ L	L ₁	В	Tensile Breaking Load *1	Mass (g)	Qty per Pack
	Nominal of Thread	Pitch							ו וט		Ь	(N)	iviass (g)	Qty per rack
SNSTA-M3	M3	0.5	6	8	10				5.5	3	2.5	1360	1.5 - 1.9	1
SNSTA-M4	M4	0.7		8	10	12			7	4	3	2370	3.4 - 4	1
SNSTA-M5	M5	0.8			10	12	16	20	8.5	5	4	3840	6.3 - 8.8	1
SNSTA-M6	M6	1				12	16	20	10	6	5	5440	11 -13	1

*1: Values in chart are for reference only. They are not guaranteed values.

• Part number specification



Please contact our customer service for the price and delivery time.

