


# SVSHS Socket Head Cap Screws with Ventilation Hole with Special Low Profile



Vacuum Protrusion Cleanroom wash & packaging SUS Stainless steel



● Application

Vacuum devices, vacuum chambers, FPD production equipment, semiconductor devices, and electron microscopes

● Material/Finish



	<b>SVSHS</b>
Main Body	SUSXM7 (Equivalent to SUS304)
Strength Class	A2-50

- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- The head height of all screws is 1.5 mm or less. These screws are intended for the reduction of the size of machinery and device and applications with limited overhead space.
- Cleanroom wash and cleanroom packing are completed. ➔ P.xxxx


Unit : mm

Part Number 1	M (Coarse)		L 2						D1	L1	B	t	d	Mass (g)	Qty per pack
	Nominal of Thread	Pitch	6	8	10	12	16	20							
<b>SVSHS-M3</b>	M3	0.5	6	8	10				6	1.3	1.5	2	1.2	0.53 - 0.7	20
<b>SVSHS-M4</b>	M4	0.7	6	8	10	12	16		8	1.5	2	2.5	1.5	1.1 - 1.9	20
<b>SVSHS-M5</b>	M5	0.8	6	8	10	12	16	20	9	1.5	3	3	1.5	1.5 - 3.3	10
<b>SVSHS-M6</b>	M6	1	6	8	10	12	16	20	10	1.5	3	4	2	2.7 - 5.3	10

● When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

● Usage example

Effective with vacuum devices and vacuum chambers that require the exhaustion of gas trapped in screw holes.



● Part number specification

**SVSHS-M5 - 20**



Individual Sales ➔ P.xxxx	Cleanroom Wash & Packaging ➔ P.xxxx	Screw Length Adjustment ➔ P.xxxx	Vibration Resistant ➔ P.xxxx	Modification process for captive use ➔ P.xxxx
Available / Add'l charge	Cleanroom washed and packed	Available / Add'l charge	Not Available	Not Available