



Date: Aug, 2026

Notice of Change to the Torque Notation Method for MOR Flexible Couplings

Dear Valued Customer,

We hope you are doing well and appreciate your continued support of NBK. As described below, for the MOR Flexible Couplings, the conventional torque notation has been stated as the value for one-directional rotation without load fluctuations. To clarify the conditions under which the torque values are applicable, we will change the notation to separately indicate the One-Directional Rotation Torque and the Forward/Reverse Rotation Torque. There will be no changes to the product structure, specifications, or materials. Your understanding and continued support of our products are greatly appreciated.

Applicable Products:

Flexible Couplings – Oldham Type
MOR / MOR-C / MOR-K / MOR-CK

Details of the Change:

- Change Nominal Torque to One-Directional Rotation Torque and Forward/Reverse Rotation Torque.
- Delete Maximum Torque.
- MOR / Flexible Couplings – Oldham Type – Set Screw Type (N·m)

	Before Change	After Change	
Part Number	Nominal Torque	One-Directional Rotation Torque *	Forward/Reverse Rotation Torque
MOR-6	0.2	0.2	0.07
MOR-8	0.5	0.5	0.13
MOR-10	0.8	0.8	0.2
MOR-12	1	1	0.34
MOR-15	1.6	1.6	0.4
MOR-17	2.2	2.2	0.74
MOR-20	3.2	3.2	0.8
MOR-26	6	6	2
MOR-30	15	15	5
MOR-34	16	16	5.4
MOR-38	28	28	7
MOR-45	30	30	10
MOR-55	45	45	15
MOR-68	80	80	20

● MOR-C / Flexible Couplings – Oldham Type – Clamping Type (N·m)

	Before Change	After Change	
Part Number	Nominal Torque	One-Directional Rotation Torque*	Forward/Reverse Rotation Torque
MOR-12C	1	1	0.34
MOR-15C	1.6	1.6	0.4
MOR-17C	2.2	2.2	0.74
MOR-20C	3.2	3.2	0.8
MOR-26C	6	6	2
MOR-30C	15	15	5
MOR-34C	16	16	5.4
MOR-38C	28	28	7
MOR-45C	30	30	10
MOR-55C	45	45	15
MOR-68C	80	80	20

● MOR-K / Flexible Couplings – Oldham Type – Set Screw + Key Type (N·m)

	Before Change	After Change	
Part Number	Nominal Torque	One-Directional Rotation Torque*	Forward/Reverse Rotation Torque
MOR-15K	1.6	1.6	0.4
MOR-17K	2.2	2.2	0.74
MOR-20K	3.2	3.2	0.8
MOR-26K	6	6	2
MOR-30K	15	15	5
MOR-34K	16	16	5.4
MOR-38K	28	28	7
MOR-45K	30	30	10
MOR-55K	45	45	15
MOR-68K	80	80	20

● MOR-CK / Flexible Couplings – Oldham Type – Clamping + Key Type (N·m)

	Before Change	After Change	
Part Number	Nominal Torque	One-Directional Rotation Torque*	Forward/Reverse Rotation Torque
MOR-15CK	1.6	1.6	0.4
MOR-17CK	2.2	2.2	0.74
MOR-20CK	3.2	3.2	0.8
MOR-26CK	6	6	2
MOR-30CK	15	15	5
MOR-34CK	16	16	5.4
MOR-38CK	28	28	7
MOR-45CK	30	30	10
MOR-55CK	45	45	15
MOR-68CK	80	80	20

* The One-Directional Rotation Torque values are based on durability test results confirming a service life of at least 1 million rotations under one-directional rotation.

For applications involving forward/reverse operation or load fluctuations, please select the product based on the Forward/Reverse Rotation Torque from now on.

Change Effective Period:

Monday, August 31, 2026

Please note that returns or exchanges related to this change will not be accepted.

If you have any questions, please contact our sales office in charge of your area.

Thank you for your understanding and cooperation.

Global, including Taiwan and Korea

NBK (Nabeya Bi-tech Kaisha)

1, Toko-Taichi, Seki City, Gifu, 501-3939, Japan

Phone: +81(575)-23-1162

North America

NBK America LLC

3500 Scotts Lane, Unit OFC01, Philadelphia, PA 19129, USA

Phone: +1 (484) 685-7500

Asia, Oceania

NBK ASIA MANAGEMENT PTE. LTD.

80 Robinson Road #10-01A Singapore 068898

Phone : +81(575)-23-7187