



● Material/Finish



	FCCA Made of Aluminum	FCCS Made of Stainless Steel
Main Body	Aluminum Alloy	SUS304
Hex Socket Set Screw	SUSXM7	SUSXM7

- The clamber joints 2 shafts with cross.
- Fix the shafts by hex socket set screws. It is superior in cost effectiveness.
- Convenient for adjustment of side guide and sensors of the conveyance line.
- Light aluminum and stainless steel with highly corrosion-resistant are standardized.
- Compatible with both round shaft and square shaft.
- All products are provided with hex socket set screw.

Unit : mm

Part Number Made of Aluminum	Mass (g)	Part Number Made of Stainless Steel	Mass (g)	D1	D2	B1	B2	A	W	P	H	M (Coarse)
FCCA-8-8	9	FCCS-8-8	27	8	8			12	32	10	11	M4
FCCA-8-10	16	FCCS-8-10	48	8	10		8	14	40	12	14	M4
FCCA-10-10	15	FCCS-10-10	45	10	10	8	8	14	40	12	14	M4
FCCA-10-12	23	FCCS-10-12	68	10	12	8	10	16	45	15	15	M5
FCCA-12-12	21	FCCS-12-12	63	12	12	10	10	16	45	15	15	M5
FCCA-10-15	41	FCCS-10-15	120	10	15	8	12	19	55	19	18	M5
FCCA-12-15	39	FCCS-12-15	115	12	15	10	12	19	55	19	18	M5
FCCA-15-15	35	FCCS-15-15	105	15	15	12	12	19	55	19	18	M5
FCCA-12-20	79	FCCS-12-20	235	12	20	10	16	25	64	24	20	M6
FCCA-15-20	75	FCCS-15-20	222	15	20	12	16	25	64	24	20	M6
FCCA-20-20	66	FCCS-20-20	194	20	20	16	16	25	64	24	20	M6

● Usage example

In combination with plastic clamp lever **LEMS**
 (→ P.xxxx) and scale sticker **FSS** (→ P.xxxx).



● Part number specification

FCCA-10-15



Cleanroom Wash & Packaging → P.xxxx	Screw Length Adjustment → P.xxxx	Vibration Resistant → P.xxxx	Laser Marking → P.xxxx
Please feel free to contact us	Not Available	Please feel free to contact us	Available / Add'l charge