



Material/Finish



 Usage Example Gas trapped at the bottom of the screw hole is released through **SVSS SVSS-PC**, and gas trapped in the drilled hole is released through SWAS-VF SWAS-VF-PC.





e-nedzi.com

- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- Cleanroom wash/cleanroom packing provided.
- Special chemical polishing treatment improves the surface roughness of **SVSS-PC**. Outgas quantity is extremely low. Ideal for use in medium vacuum environments.
- Ventilation holes are machined using a method with minimal effect on metallic structures. Brittle fracture and outgassing during use in vacuum environments are prevented.

Application

Vacuum devices, vacuum chambers, FPD production equipment. semiconductor devices, and electron microscopes

	Unit: mm																												
	rait Nullibel	M (Coarse)			L 12														D ₁ I	1.	В	d	Mass (g)		Oty per Back				
		Nominal of Thread	Pitch																				וט	LI	Ь	u	ivia	ss (g)	Qty per rack
SVSS-M2		M2	0.4	3	4 5	6	8	10															3.8	2	1.5	0.8	0.10	5 - 0.3	10
SVSS-M2.5		M2.5	0.45		4 5	6	8	10	12														4.5	2.5	2	1	0.3	5 - 0.59	10
SVSS-M3	SVSS-M3-PC	M3	0.5		5	6	8	10	12	14	15	16	18										5.5	3	2.5	1.2	0.6	7- 1.3	20
SVSS-M4	SVSS-M4-PC	M4	0.7		5	6	8	10	12	14	15	16	18	20	22	25	30	35					7	4	3	1.5	1.4	- 4.2	20*1
SVSS-M5	SVSS-M5-PC	M5	0.8			6	8	10	12	14	15	16	18	20	22	25	30	35	40				8.5	5	4	1.5	2.2	- 7.1	10
SVSS-M6	SVSS-M6-PC	M6	1				8	10	12	14	15	16	18	20	22	25	30	35	40	45	50		10	6	5	2	4.3	- 13	10
SVSS-M8	SVSS-M8-PC	M8	1.25						12			16		20		25	30	35	40	45	50	60	13	8	6	2	11	- 29	10*2
SVSS-M10	SVSS-M10-PC	M10	1.5									16		20		25	30	35	40	45	50	60	16	10	8	3	21	- 46	5
SVSS-M12	SVSS-M12-PC	M12	1.75														30	35	40	45	50	60	18	12	10	3	39	- 63	5

- *1: Quantity per pack for $\boxed{\text{SVSS-M4-30}}$, $\boxed{\text{SVSS-M4-35-PC}}$, and $\boxed{\text{SVSS-M4-35-PC}}$ is 10.
- *2: Quantity per pack for **SVSS-M8-60** and **SVSS-M8-60-PC** is 5.
- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

Related Products

For ventilation of drilled holes. please use **SWAS-VF** SWAS-VF-PC



• Part Number Specification



1 Individual Sales

🥵 Cleanroom Wash & Packaging 🔐 Screw Length Adjustment 🚅 Vibration Resistant





Modification process for captive use Please feel free to contact us