

MOL/MOS Flexible Couplings - Oldham Type

⚡ Electrical Insulation ⚙️ High Allowable Misalignment ⚙️ Small Eccentric Reaction Force

Structure

• Set Screw Type

MOL Outside diameter $\phi 16 - \phi 32 \rightarrow$ P.xxxx

Hex socket set screw



MOL Outside diameter $\phi 40 - \phi 63$




MOS $\rightarrow$ P.xxxx



• Clamping Type


MOL-C Outside diameter $\phi 16 - \phi 32 \rightarrow$ P.xxxx



MOL-C Outside diameter $\phi 40 - \phi 63$



MOS-C $\rightarrow$ P.xxxx



• Applicable motors

	MOL	MOS
Servomotor	—	—
Stepping Motor	—	—
General-purpose Motor	⊙	⊙

⊙: Excellent

• Property

	MOL	MOS
Allowable Misalignment	⊙	⊙
Electrical Insulation	⊙	⊙
Allowable Operating Temperature	−20°C to 80°C	−20°C to 80°C

⊙: Excellent ○: Very good

- This is an oldham type flexible coupling.
- Slippage of hubs and a spacer allows large eccentricity and angular misalignment to be accepted.
- The load on the shaft generated by misalignment is small and the burden on the shaft is reduced.
- It has electrical insulation.
- Standard type **MOL** and short type **MOS** are available.
- Application

Parts feeder / Transport device

• Material/Finish

RoHS

	MOL / MOL-C / MOS / MOS-C
Hub	A2017 Anodized*1
Spacer	Polyacetal
Hex Socket Set Screw	SCM435 Ferrosoferric Oxide Film (Black)
Hex Socket Head Cap Screw	SCM435 Ferrosoferric Oxide Film (Black)

*1: Due to manufacturing process requirements, couplings may have bores with or without surface treatment. This does not affect the performance of the couplings.

• Slip Torque

For set screw type **MOL** **MOS**, see Aluminum Alloy Coupling under "Slip Torque of Coupling - Set Screw Type" for details.

• Part number specification

MOL-20C-6-8

Product Code Size Bore Diameter

Please refer to dimensional table for part number specification.

⚙️ Additional Keyway at Shaft Hole $\rightarrow$ P.xxxx

⚙️ Cleanroom Wash & Packaging $\rightarrow$ P.xxxx

⚙️ Change to Stainless Steel Screw $\rightarrow$ P.xxxx


Available / Add'l charge

Please feel free to contact us

Available / Add'l charge

MOL/MOL-C Flexible Couplings - Oldham Type - Set Screw Type / Clamping Type

⚡ Electrical Insulation ⚙️ High Allowable Misalignment ⚙️ Small Eccentric Reaction Force



Dimensions

Unit : mm

Part Number	A	L	W	E	F	G	M	Screw Tightening Torque (N·m)
MOL-16	16	7	18	7	3.5		M3	0.7
MOL-20	20	9	23	9	4.5		M4	1.7
MOL-25	25	11	28.2	11	5.5		M5	4
MOL-32	32	12.7	32.7	14.5	6.5		M6	7
MOL-40	40	14	32	17	7		M6	7
MOL-50	50	17	38.2	23	8.5		M8	15
MOL-63	63	21	46.6	28	10.5		M10	30
MOL-16C	16	12.5	29	7	3	5	M2.5	1
MOL-20C	20	14.4	33.8	9	3	6.5	M2.5	1
MOL-25C	25	16.5	39.2	11	3.8	9	M3	1.5
MOL-32C	32	18.7	44.7	14.5	4.5	11	M4	2.5
MOL-40C	40	23	50	17	7	13	M5	4
MOL-50C	50	27	58.2	23	8	16	M6	8
MOL-63C	63	33	70.6	28	10	21	M8	16

Part Number	Standard Bore Diameter D1/D2															
	3	4	5	6	6.35	8	9.525	10	11	12	14	15	16	18	20	25
MOL-16	●	●	●	●	●	●										
MOL-20		●	●	●	●	●										
MOL-25			●	●	●	●	●	●								
MOL-32				●	●	●	●	●	●	●	●					
MOL-40					●	●		●	●	●	●	●	●	●	●	
MOL-50						●			●	●	●	●	●	●	●	●
MOL-63											●	●	●	●	●	●
MOL-16C			●	●	●	●										
MOL-20C				●	●	●										
MOL-25C					●	●	●	●	●	●	●					
MOL-32C						●		●	●	●	●	●	●	●	●	●
MOL-40C									●	●	●	●	●	●	●	●
MOL-50C											●	●	●	●	●	●
MOL-63C												●	●	●	●	●


- All products are provided with hex socket set screw [MOL] or hex socket head cap screw [MOL-C].
- Tolerance of shaft bore on set screw type [MOL] is H8.
- Recommended tolerance for shaft diameters is h6 and h7.
- A set of hubs with set screw type for one side and clamping type for the other side is available upon request.
- For the shaft insertion amount to the coupling, see Mounting/maintenance.

Additional Keyway at Shaft Hole → P.xxxx Cleanroom Wash & Packaging → P.xxxx Change to Stainless Steel Screw → P.xxxx

Available / Add'l charge

Please feel free to contact us

Available / Add'l charge

[MOL-C] Outside diameter $\phi 16 - \phi 32$ [MOL-C] Outside diameter $\phi 40 - \phi 63$


Performance

Part Number	Max. Bore Diameter (mm)	Rated Torque *1 (N·m)	Maximum Torque *1 (N·m)	Max. Rotational Frequency (min ⁻¹)	Moment of Inertia *2 (kg·m ²)	Static Torsional Stiffness (N·m/rad)	Max. Lateral Misalignment (mm)	Max. Angular Misalignment (°)	Mass *2 (g)
MOL-16	6.35	0.7	1.4	39000	3.2×10^{-7}	31	1	3	7
MOL-20	8	1.2	2.4	31000	1.0×10^{-6}	60	1.5	3	14
MOL-25	10	2	4	25000	3.0×10^{-6}	140	2	3	27
MOL-32	14	4.5	9	19000	9.5×10^{-6}	280	2.5	3	50
MOL-40	16	9	18	15000	2.3×10^{-5}	540	3	3	80
MOL-50	20	18	36	12000	6.7×10^{-5}	820	3.5	3	150
MOL-63	25	36	72	10000	2.2×10^{-4}	1900	4	3	300
MOL-16C	6	0.7	1.4	39000	5.8×10^{-7}	31	1	3	12
MOL-20C	8	1.2	2.4	31000	1.5×10^{-6}	60	1.5	3	19
MOL-25C	10	2	4	25000	4.4×10^{-6}	140	2	3	36
MOL-32C	14	4.5	9	19000	1.4×10^{-5}	280	2.5	3	69
MOL-40C	16	9	18	15000	4.1×10^{-5}	540	3	3	130
MOL-50C	20	18	36	12000	1.2×10^{-4}	820	3.5	3	230
MOL-63C	25	36	72	10000	3.7×10^{-4}	1900	4	3	450

*1 : Values with no load fluctuation and rotation in a single direction. If there is large load fluctuation, or both normal and reverse rotation, select a size with some margin. If ambient temperature exceeds 30°C, be sure to correct the rated torque and max. torque with temperature correction factor shown in the following table. The allowable operating temperature of [MOL] and [MOL-C] is -20°C to 80°C.

*2 : These are values with max. bore diameter.

Comparison of rated torque



Precautions for Use

- In case of mounting on D-cut shaft, be careful about the position of the D-cut surface of the shaft. → P.xxxx
- There are sizes where the hex socket head bolt exceeds the outer diameter of the coupling and the rotating diameter is larger than the outer diameter. Please be careful of the interference of coupling. → P.xxxx

Ambient Temperature / Temperature Correction Factor

Ambient Temperature	Temperature Correction Factor
-20°C to 30°C	1.00
30°C to 40°C	0.80
40°C to 60°C	0.70
60°C to 80°C	0.55

Part number specification

MOL-40C-14-15 **1 Set**

MOL-40 - SPCR **Single Spacer**

Product Code Outside Diameter (Dimension A) Single Spacer